NSN 5985-00-111-4881

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-111-4881

| Application Design: |
|---|
| Transmission line |
| Body Material: |
| Metal |
| Body Style: |
| Round, terminal/terminals in opposite surface |
| Body Surface Treatment: |
| Silver plated |
| Overall Length: |
| 2.200 inches |
| Overall Diameter: |
| 0.625 inches |
| Operating Tempurature Range: |
| +0.0/+65.0 degrees celsius |
| Voltage Standing Wave Ratio: |
| 1.15 |
| Input Impedance Rating In Ohms: |
| 50.0 |
| Output Impedance Rating In Ohms: |
| 50.0 |
| Coaxial Connector Series Designation: |
| |
| Bnc |
| Bnc Power Rating: |
| |
| Power Rating: |
| Power Rating: 2.0 watts average |
| Power Rating: 2.0 watts average Rf Signal Attenuation In Decibels: |
| Power Rating: 2.0 watts average Rf Signal Attenuation In Decibels: 3.0 |
| Power Rating: 2.0 watts average Rf Signal Attenuation In Decibels: 3.0 Voltage Standing Wave Ratio Frequency Range: |
| Power Rating: 2.0 watts average Rf Signal Attenuation In Decibels: 3.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+30.0 megahertz |
| Power Rating: 2.0 watts average Rf Signal Attenuation In Decibels: 3.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+30.0 megahertz Attenuation Accuracy In Decibels: |
| Power Rating: 2.0 watts average Rf Signal Attenuation In Decibels: 3.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+30.0 megahertz Attenuation Accuracy In Decibels: -0.009/+0.009 |
| Power Rating: 2.0 watts average Rf Signal Attenuation In Decibels: 3.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+30.0 megahertz Attenuation Accuracy In Decibels: -0.009/+0.009 Connection Type Per Function: |
| Power Rating: 2.0 watts average Rf Signal Attenuation In Decibels: 3.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+30.0 megahertz Attenuation Accuracy In Decibels: -0.009/+0.009 Connection Type Per Function: Female input and male output |
| Power Rating: 2.0 watts average Rf Signal Attenuation In Decibels: 3.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+30.0 megahertz Attenuation Accuracy In Decibels: -0.009/+0.009 Connection Type Per Function: Female input and male output Mounting Method: |
| Power Rating: 2.0 watts average Rf Signal Attenuation In Decibels: 3.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+30.0 megahertz Attenuation Accuracy In Decibels: -0.009/+0.009 Connection Type Per Function: Female input and male output Mounting Method: Terminal |
| Power Rating: 2.0 watts average Rf Signal Attenuation In Decibels: 3.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+30.0 megahertz Attenuation Accuracy In Decibels: -0.009/+0.009 Connection Type Per Function: Female input and male output Mounting Method: Terminal Terminal Type And Quantity: |
| Power Rating: 2.0 watts average Rf Signal Attenuation In Decibels: 3.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+30.0 megahertz Attenuation Accuracy In Decibels: -0.009/+0.009 Connection Type Per Function: Female input and male output Mounting Method: Terminal Terminal Type And Quantity: 2 connector |
| Power Rating: 2.0 watts average Rf Signal Attenuation In Decibels: 3.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+30.0 megahertz Attenuation Accuracy In Decibels: -0.009/+0.009 Connection Type Per Function: Female input and male output Mounting Method: Terminal Terminal Type And Quantity: 2 connector Frequency Range: |
| Power Rating: 2.0 watts average Rf Signal Attenuation In Decibels: 3.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+30.0 megahertz Attenuation Accuracy In Decibels: -0.009/+0.009 Connection Type Per Function: Female input and male output Mounting Method: Terminal Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 30.000 megahertz |
| Power Rating: 2.0 watts average Rf Signal Attenuation In Decibels: 3.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+30.0 megahertz Attenuation Accuracy In Decibels: -0.009/+0.009 Connection Type Per Function: Female input and male output Mounting Method: Terminal Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 30.000 megahertz Precious Material And Location: |

NSN 5985-00-111-4881

Fixed Attenuator - Page 2 of 2



Test Data Document:

12436-810002-693 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A20000