

View Online at <https://aerobasegroup.com/nsn/5985-00-113-5025>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Direction:

Right-hand all flanges single connection facility

Tubing Wall Construction Style:

Interlocked single tubing segment

Tubing Twist Type:

Twistable single tubing segment

Tubing Twist Angle In Deg:

3000.0 single tubing segment

Flange Quantity:

2

Flange Inside Width:

0.622 inches all flanges

Flange Inside Height:

0.311 inches all flanges

Flange Outside Width:

1.312 inches all flanges

Flange Outside Height:

1.312 inches all flanges

Flange Depth:

0.375 inches all flanges

Voltage Standing Wave Ratio:

1.15

Insertion Loss In Decibels:

0.20

Maximum Operating Pressure:

60.0 pounds per square inch gage

Waveguide Outside Width:

0.702 inches

Thread Size:

0.138 inches all flanges single connection facility

Waveguide Inside Width:

0.622 inches

Waveguide Inside Height:

0.311 inches

Waveguide Outside Height:

0.391 inches

Flange Connecting Facility And Quantity:

4 threaded hole all flanges single connection facility

Flange Style:

Choke type all flanges

Waveguide Length:

1.000 feet

Flexibility:

Flexible single tubing segment

Material:

Rubber single tubing jacket

Precious Material And Location:

Tubing interior and exterior, flange interior and exterior silver

Precious Material:

Silver

Surface Treatment:

Silver single tubing segment all surfaces

Style Designator:

Straight type

Thread Series Designator:

Unc all flanges single connection facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A073a0