NSN 5985-00-113-6787

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-113-6787

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange all connection facilities

Thread Direction:

Right-hand first flange all connection facilities

Bend Angle In Deg:

90.0 single bend h-plane

Tubing Wall Construction Style:

Convolute all tubing segment

Flange Quantity:

2

Flange Inside Width:

1.003 inches second flange

Flange Inside Height:

0.505 inches second flange

Flange Outside Width:

1.625 inches second flange

Flange Outside Height:

1.625 inches first flange

Flange Depth:

0.438 inches second flange

Flange Connecting Hole Diameter:

0.169 inches second flange all connection facilities

Voltage Standing Wave Ratio:

1.10

Thready Qty Per Inch (tpi):

32 first flange all connection facilities

Maximum Operating Pressure:

15.0 pounds per square inch gage

Waveguide Outside Width:

1.000 inches

Thread Size:

0.164 inches first flange all connection facilities

Waveguide Inside Width:

0.900 inches

Waveguide Inside Height:

0.400 inches

Waveguide Outside Height:

0.500 inches

Waveguide Longer Offset Distance:

1.895 inches

NSN 5985-00-113-6787

Waveguide Assembly - Page 2 of 2



Flange Connecting Facility And Quantity: 4 unthreaded hole second flange all connection facilities Flange Style: Cover type second flange Flexibility: Rigid all tubing segment Material: Aluminum all flange **Precious Material And Location:** Tubing and flange internal surfaces silver **Precious Material:** Silver **Surface Treatment:** Silver all tubing segment and flange inside surfaces **Style Designator:** Bend type **Thread Series Designator:** Unc first flange all connection facilities Shelf Life: N/a **Unit Of Measure:** Demilitarization: No

Fiig: A073a0