NSN 5985-00-116-3842

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-116-3842

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
2.250 inches
Overall Height:
2.031 inches
Overall Width:
7.000 inches
Operating Tempurature Range:
-10.0 to 70.0 degrees celsius
Voltage Standing Wave Ratio:
1.20
Coaxial Connector Series Designation:
Bnc
Power Rating:
500.0 milliwatts peak
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.1
Overall Attenuation Range In Decibels:
+2.0 to 60.0
Attenuation Accuracy Reference Frequency:
250.0 megahertz
Attenuation Variation Method:
Stepped
Step Position Quantity:
6
Attenuation Per Step In Decibels:
2.0 and 3.0 and 5.0 and 10.0 and 20.0 and 20.0
Mounting Facility Type And Quantity:
2 connector
Frequency Range:
Between 70.000 megahertz and 460.000 megahertz
Overall Attenuation Accuracy In Decibels:
-0.50 to 0.50
Adjustment Device Type And Quantity:
6 lever
Impedance Rating In Ohms:
50.0 input-output
Terminal Type And Quantity:

1 connector, coaxial, male and 1 connector, coaxial, female

NSN 5985-00-116-3842

Variable Attenuator - Page 2 of 2



				-
C I	20	lŧ.	l i	fe:
J.	16		_,	ıc.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A223a0