

View Online at <https://aerobasegroup.com/nsn/5985-00-118-7985>

**Application Design:**

Transmission line

**Body Material:**

Aluminum

**Body Style:**

Round, terminal/terminals in opposite surface

**Body Surface Treatment:**

Any acceptable

**Overall Length:**

2.660 inches

**Overall Diameter:**

0.812 inches

**Voltage Standing Wave Ratio:**

1.20 and 1.25

**Input Impedance Rating In Ohms:**

50.0

**Output Impedance Rating In Ohms:**

50.0

**Coaxial Connector Series Designation:**

N

**Power Rating:**

2.0 watts average and 300.0 kilowatts peak

**Rf Signal Attenuation In Decibels:**

6.0

**Voltage Standing Wave Ratio Frequency Range:**

+0.0/+6.0 gigahertz and +6.0 to 12.4 gigahertz

**Attenuation Accuracy Reference Frequency:**

12.4 gigahertz

**Attenuation Accuracy In Decibels:**

-0.30 to 0.30

**Connection Type Per Function:**

Female output and male input

**Unpackaged Unit Weight:**

2.400 ounces

**Mounting Method:**

Connector

**Terminal Type And Quantity:**

2 connector

**Frequency Range:**

Between 0.000 gigahertz and 12.400 gigahertz

**Fsc Application Data:**

Antennas, waveguides, and related equipment

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A20000