NSN 5985-00-120-8718

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-120-8718

Application Design:	
Transmission line	
Body Material:	
Aluminum alloy	
Body Style:	
Coaxial type	
Overall Length:	
Between 5.410 inches and 5.	490 inches
Center To Center Distance	Between Mounting Facilities Parallel To Length:
3.540 inches	
Center To Center Distance	Between Mounting Facilities Parallel To Width:
2.230 inches	
Overall Height:	
2.990 inches	
Overall Width:	
Between 1.265 inches and 1.	285 inches
Unthreaded Mounting Hole	Diameter:
0.156 inches	
Voltage Standing Wave Rat	io:
1.50	
Coaxial Connector Series D	Designation:
N	
Overall Attenuation Range	In Decibels:
+0.7/+40.0	
Attenuation Variation Metho	od:
Continuous	
Mounting Facility Type And	I Quantity:
4 unthreaded hole	
Frequency Range:	
Between 2.700 gigahertz and	I 2.900 gigahertz
Adjustment Device Type Ar	nd Quantity:
1 electronic, voltage controlle	ed
Mounting Facility Pattern:	
Four position rectangular	
Impedance Rating In Ohms	:
50.0 output	
Special Features:	
Voltage to attenuation charac	cteristics shall be linear from 0.7 db to a m in of 40.0 db; exterior finish shall be brown to match federal standard
595 color number 30372	
Terminal Type And Quantity	y:
1 connector, coaxial, female	and 1 connector, coaxial, male and 1 connector, receptacle
Fsc Application Data:	
Antonnoo waxaquidaa and r	

Antennas, waveguides, and related equipment

NSN 5985-00-120-8718

Variable Attenuator - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A223a0

