

View Online at <https://aerobasegroup.com/nsn/5985-00-124-5250>

**Cross Sectional Shape:**

Internal, rectangular external, rectangular

**Thread Class:**

2b first flange all connection facilities

**Thread Direction:**

Right-hand first flange all connection facilities

**Tubing Wall Construction Style:**

Corrugated single tubing segment

**Flange Quantity:**

2

**Flange Inside Width:**

1.253 inches second flange and 1.256 inches second flange

**Flange Inside Height:**

0.628 inches second flange and 0.631 inches second flange

**Flange Outside Width:**

1.860 inches second flange and 1.890 inches second flange

**Flange Outside Height:**

1.860 inches second flange and 1.890 inches second flange

**Flange Inside Diameter:**

1.610 inches first flange and 1.640 inches first flange

**Flange Depth:**

0.610 inches first flange and 0.640 inches first flange

**Flange Connecting Hole Diameter:**

0.169 inches second flange all connection facilities and 0.172 inches second flange all connection facilities

**Voltage Standing Wave Ratio:**

1.05

**Maximum Operating Pressure:**

5.0 pounds per square inch gage

**Waveguide Outside Width:**

1.250 inches

**Thread Size:**

0.164 inches first flange all connection facilities

**Waveguide Inside Width:**

1.122 inches

**Waveguide Inside Height:**

0.497 inches

**Waveguide Outside Height:**

0.625 inches

**Flange Connecting Facility And Quantity:**

4 unthreaded hole second flange all connection facilities

**Flange Style:**

Cover type second flange

**Waveguide Length:**

Between 4.200 inches and 4.300 inches

**Flexibility:**

Flexible single tubing segment

**Material:**

Copper alloy single tubing segment

**Style Designator:**

Straight type

**Thread Series Designator:**

Unc first flange all connection facilities

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A073a0