NSN 5985-00-132-6897

Fixed Attenuator - Page 1 of 2

Application Design: Transmission line



View Online at https://aerobasegroup.com/nsn/5985-00-132-6897

Body Material:
Brass, qq-b-626, comp 22, 1/2h
Body Style:
Round, terminal/terminals in opposite surface
Body Surface Treatment:
Silver plated
Overall Length:
2.688 inches
Overall Diameter:
0.813 inches
Operating Tempurature Range:
-55.0 to 125.0 degrees celsius
Voltage Standing Wave Ratio:
1.20 and 1.25
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
N
Power Rating:
2.0 watts average and 300.0 watts peak
Rf Signal Attenuation In Decibels:
3.0
Voltage Standing Wave Ratio Frequency Range:
+0.0 to 3.0 gigahertz and +3.0/+6.0 gigahertz
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 6.000 gigahertz
Special Features:
Fungus resistant per mil-e-5272 procedure 1
Precious Material And Location:
Body surface silver
Precious Material:
Silver
Fsc Application Data:
Antennas, waveguides, and related equipment
Shelf Life:
N/a

NSN 5985-00-132-6897

Fixed Attenuator - Page 2 of 2



	Of			

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000