## NSN 5985-00-133-2927

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-133-2927

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
6.562 inches
Overall Height:
1.687 inches
Overall Width:
1.687 inches
Operating Tempurature Range:
-20.0 to 125.0 degrees celsius
Voltage Standing Wave Ratio:
1.30
Coaxial Connector Series Designation:
Bnc
Power Rating:
500.0 milliwatts average and 1.0 kilowatts peak
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.3
Overall Attenuation Range In Decibels:
+0.0/+82.5
Attenuation Variation Method:
Stepped
Step Position Quantity:
9
Attenuation Per Step In Decibels:
0.5 and 1.0 and 2.0 and 3.0 and 6.0 and 10.0 and 20.0 and 20.0 and 20.0
Mounting Facility Type And Quantity:
2 connector
Frequency Range:
Between 0.000 megahertz and 500.000 megahertz
Overall Attenuation Accuracy In Decibels:
-1.00 to 1.00
Adjustment Device Type And Quantity:
9 lever
Impedance Rating In Ohms:
75.0 input-output
Terminal Type And Quantity:
2 connector, coaxial, female
Shelf Life:

N/a

## NSN 5985-00-133-2927

Variable Attenuator - Page 2 of 2



**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0