## NSN 5985-00-134-9901

Fixed Attenuator - Page 1 of 2

**Application Design:** 



View Online at https://aerobasegroup.com/nsn/5985-00-134-9901

Transmission line
Body Material:
Metal
Body Style:
Round, terminal/terminals in opposite surface
Body Surface Treatment:
Any acceptable
Overall Length:
2.660 inches
Overall Diameter:
0.625 inches
Voltage Standing Wave Ratio:
1.20 and 1.25
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
N
Power Rating:
2.0 watts average and 300.0 watts peak
Rf Signal Attenuation In Decibels:
1.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+3.0 gigahertz and +3.0 to 6.0 gigahertz
Attenuation Accuracy Reference Frequency:
6.0 gigahertz
Attenuation Accuracy In Decibels:
-0.50 to 0.50
Connection Type Per Function:
Female input and male output
Unpackaged Unit Weight:
2.400 ounces
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 6.000 gigahertz
Shelf Life:
N/a

## NSN 5985-00-134-9901

Fixed Attenuator - Page 2 of 2



	Of			

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000