## NSN 5985-00-134-9902

Fixed Attenuator - Page 1 of 2



-134-9902

View Online at https://aerobasegroup.com/nsn/5985-0	)0-
Application Design:	
Transmission line	
Body Material:	
Brass, qq-b-626, comp 22, 1/2h	
Body Style:	
Round, terminal/terminals in opposite surface	
Body Surface Treatment:	
Silver plated, qq-s-365	
Overall Length:	
2.688 inches	
Overall Diameter:	
0.813 inches	
Operating Tempurature Range:	
-55.0/+125.0 degrees celsius	
Voltage Standing Wave Ratio:	
1.20 and 1.25	
Input Impedance Rating In Ohms:	
50.0	
Output Impedance Rating In Ohms:	
50.0	
Coaxial Connector Series Designation:	
N	
Power Rating:	
2.0 watts average and 300.0 watts peak	
Rf Signal Attenuation In Decibels:	
6.0	
Voltage Standing Wave Ratio Frequency Range:	
+0.0 to 3.0 gigahertz and +3.0/+6.0 gigahertz	
Attenuation Accuracy Reference Frequency:	
6.0 gigahertz	
Attenuation Accuracy In Decibels:	
-0.50 to 0.50	
Connection Type Per Function:	
Female output and male input	
Unpackaged Unit Weight:	
2.400 ounces	
Mounting Method:	
Connector	
Terminal Type And Quantity:	
2 connector	
Frequency Range:	

Between 0.000 hertz and 6.000 gigahertz

## **NSN 5985-00-134-9902** Fixed Attenuator - Page 2 of 2



Precious Material And Location:
Body surface silver
Precious Material:
Silver
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A20000