NSN 5985-00-135-4056

Fixed Attenuator - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5985-00-135-4056



Application Design:

Transmission line

Body Material:

Steel

Body Style:

Round, terminal/terminals in opposite surface

Body Surface Treatment:

Any acceptable

Overall Length:

2.660 inches

Overall Diameter:

0.812 inches

Voltage Standing Wave Ratio:

1.30

Input Impedance Rating In Ohms:

50.0

Output Impedance Rating In Ohms:

50.0

Coaxial Connector Series Designation:

Ν

Power Rating:

2.0 watts average and 300.0 watts peak

Rf Signal Attenuation In Decibels:

3.0

Voltage Standing Wave Ratio Frequency Range:

+0.0/+10.0 gigahertz

Attenuation Accuracy Reference Frequency:

10.0 gigahertz

Attenuation Accuracy In Decibels:

-0.75 to 0.75

Connection Type Per Function:

Female output and male input

Unpackaged Unit Weight:

2.400 ounces

Mounting Method:

Connector

Terminal Type And Quantity:

2 connector

Frequency Range:

Between 0.000 hertz and 10.000 gigahertz

Fsc Application Data:

Antennas, waveguides, and related equipment

NSN 5985-00-135-4056

Fixed Attenuator - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A20000

