NSN 5985-00-135-4057

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-135-4057

Application Design:
Transmission line
Body Material:
Steel
Body Style:
Round, terminal/terminals in opposite surface
Body Surface Treatment:
Any acceptable
Overall Length:
2.660 inches
Overall Diameter:
0.812 inches
Voltage Standing Wave Ratio:
1.30
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
N
Power Rating:
2.0 watts average and 300.0 watts peak
Rf Signal Attenuation In Decibels:
6.0
Voltage Standing Wave Ratio Frequency Range:
+0.0 to 10.0 gigahertz
Attenuation Accuracy Reference Frequency:
10.0 gigahertz
Attenuation Accuracy In Decibels:
-0.75 to 0.75
Connection Type Per Function:
Female output and male input
Unpackaged Unit Weight:
2.400 ounces
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 10.000 gigahertz
Fsc Application Data:
Antennas, waveguides, and related equipment

NSN 5985-00-135-4057

Fixed Attenuator - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A20000