## NSN 5985-00-135-4058

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-135-4058

g
Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
4.8280 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
4.500 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
3.969 inches
Overall Height:
1.750 inches
Overall Width:
4.281 inches
Voltage Standing Wave Ratio:
1.25
Coaxial Connector Series Designation:
N
Power Rating:
10.0 watts average
Mounting Facility Screw Thread Series Designator:
Unc
Overall Attenuation Range In Decibels:
+0.0/+20.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
4 threaded hole
Frequency Range:
Between 4.000 gigahertz and 8.000 gigahertz
Mounting Thread Quantity:
32 per inch
Adjustment Device Type And Quantity:
1 knob
Mounting Facility Pattern:
Four position rectangular
Mounting Facility Screw Thread Diameter:
0.138 inches
Impedance Rating In Ohms:
50.0 input-output
Terminal Type And Quantity:

2 connector, coaxial, female

## NSN 5985-00-135-4058

Variable Attenuator - Page 2 of 2



Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0