

View Online at <https://aerobasegroup.com/nsn/5985-00-137-2793>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange all connection facilities

Thread Direction:

Right-hand first flange all connection facilities

Bend Angle In Deg:

90.0 second bend h-plane

Tubing Wall Construction Style:

Seamless all tubing segment

Flange Quantity:

2

Flange Inside Width:

0.620 inches first flange and 0.624 inches first flange

Flange Inside Height:

0.309 inches first flange and 0.313 inches first flange

Flange Outside Width:

1.297 inches first flange and 1.327 inches first flange

Flange Outside Height:

1.297 inches first flange and 1.327 inches first flange

Flange Inside Diameter:

0.985 inches first flange and 1.015 inches first flange

Flange Depth:

0.360 inches first flange and 0.390 inches first flange

Voltage Standing Wave Ratio:

1.20

Insertion Loss In Decibels:

0.50

Waveguide Outside Width:

Between 0.699 inches and 0.705 inches

Thread Size:

0.138 inches first flange all connection facilities

Waveguide Inside Width:

Between 0.620 inches and 0.625 inches

Waveguide Inside Height:

Between 0.309 inches and 0.314 inches

Waveguide Outside Height:

Between 0.388 inches and 0.394 inches

Flange Connecting Facility And Quantity:

4 threaded hole first flange all connection facilities

Flange Style:

Choke type first flange

Waveguide Length:

1.000 inches

Waveguide Center To Center Distance:

6.760 inches

Flexibility:

Rigid all tubing segment

Material:

Metal all tubing segment and flange

Surface Treatment:

Chromate all tubing segment and flange outside surfaces and enamel all tubing segment and flange outside surfaces and primer all tubing segment and flange outside surfaces

Style Designator:

Offset bend type

Thread Series Designator:

Unc first flange all connection facilities

Fsc Application Data:

Antennas waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A073a0