## NSN 5985-00-137-4328

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-137-4328

Application Design:
Transmission line
Body Material:
Aluminum
Body Style:
Coaxial type
Overall Length:
5.000 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
4.000 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.000 inches
Overall Height:
3.000 inches
Overall Width:
0.625 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.500 inches
Unthreaded Mounting Hole Diameter:
0.147 inches
Operating Tempurature Range:
+0.0/+60.0 degrees celsius
Voltage Standing Wave Ratio:
2.00
Coaxial Connector Series Designation:
Bn
Power Rating:
2.0 watts average
Insertion Loss At Minimum Attenuation In Maximum Decibels:
2.3
Overall Attenuation Range In Decibels:
+2.3/+40.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
4 unthreaded hole
Frequency Range:
Between 4.000 gigahertz and 8.000 gigahertz
Adjustment Device Type And Quantity:

1 shaft

## NSN 5985-00-137-4328

Variable Attenuator - Page 2 of 2



Mounting Facility Pattern:
Four position rectangular
Shaft Type:
Round
Impedance Rating In Ohms:
50.0 input-output
Terminal Type And Quantity:
3 connector, coaxial, female
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A223a0