

View Online at <https://aerobasegroup.com/nsn/5985-00-138-3296>

Body Style:

Rectangular

Overall Length:

1.425 inches

Overall Height:

0.500 inches

Overall Width:

1.500 inches

Frequency Rating:

0.0 gigahertz and 12.0 gigahertz single frequency operating
0.0 gigahertz and 12.0 gigahertz single frequency voltage standing wave ratio
0.0 gigahertz and 12.0 gigahertz single frequency insertion loss reference
0.0 gigahertz and 12.0 gigahertz single frequency crosstalk reference

Unthreaded Mounting Hole Diameter:

0.094 inches

Switch Type:

Nontransfer

Distance Between Mounting Facility Centers:

1.310 inches single mounting facility pattern

Operating Temperature Range:

-54.0 to 85.0 degrees celsius

Voltage Standing Wave Ratio:

1.50 single

Insertion Loss In Decibels:

0.50 single

Coaxial Connector Series Designation:

Sma

Connector End Design:

Female

Minimum Crosstalk Rating In Decibels:

60.0 single

Actuator Operating Method:

Relay

Actuator Current Type And Rating In Amps:

0.2 dc

Actuator Voltage In Volts:

Between 24.0 and 30.0

Switch Operation Sequence:

Breaks before makes

Switching Time:

12.0 milliseconds

Switch Return Mechanism Type:

Fail-safe

Pole Quantity:

1

Throw Quantity:

2

Coupling Position Quantity:

3

Mounting Facility Type And Quantity:

2 unthreaded hole

Mounting Facility Pattern:

Two position in-line single mounting facility pattern

Material:

Aluminum body

Surface Treatment:

Nickel body outside surfaces

Terminal Type And Quantity:

3 solder stud and 3 receptacle, coaxial

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A158a0