NSN 5985-00-138-7098

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-138-7098

Transmission line Body Material: Metal Body Style: Round, terminal/terminals in opposite surface Body Surface Treatment: Silver plated Overall Length: 2.200 inches Overall Diameter: 0.650 inches Operating Tempurature Range: +0.0 to 80.0 degrees celsius Voltage Standing Wave Ratio: 1.30 Input Impedance Rating In Ohms: 50.0 Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: Tnc Power Rating: 2.0 watts average and 2.5 kilowatts peak Rf Signal Attenuation In Decibels: 10.0 Voltage Standing Wave Ratio Frequency Range: +0.0 to 5.0 gigahertz Attenuation Accuracy In Decibels: -0.50/+0.50 Frequency Sensitivity Attenuation In Decibels: 0.80 Temperature Sensitivity Attenuation In Decibels: 0.0005 Connection Type Per Function: Female input and male output Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 750.000 megahertz	Application Design:
Metal Body Style: Round, terminal/terminals in opposite surface Body Surface Treatment: Silver plated Overall Length: 2.200 inches Overall Diameter: 0.650 inches Operating Tempurature Range: +0.0 to 80.0 degrees celsius Voltage Standing Wave Ratio: 1.30 Input Impedance Rating In Ohms: 50.0 Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: Tnc Power Rating: 2.0 watts average and 2.5 kilowatts peak Rf Signal Attenuation In Decibels: 10.0 Voltage Standing Wave Ratio Frequency Range: +0.0 to 5.0 gigahertz Attenuation Accuracy In Decibels: 0.80 Temperature Sensitivity Attenuation In Decibels: 0.80 Temperature Sensitivity Attenuation In Decibels: 0.0005 Connection Type Per Function: Female input and male output Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range:	Transmission line
Body Style: Round, terminal/terminals in opposite surface Body Surface Treatment: Silver plated Overall Length: 2.200 inches Overall Diameter: 0.650 inches Operating Tempurature Range: +0.0 to 80.0 degrees celsius Voltage Standing Wave Ratio: 1.30 Input Impedance Rating In Ohms: 50.0 Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: Tnc Power Rating: 2.0 watts average and 2.5 kilowatts peak Rf Signal Attenuation In Decibels: 10.0 Voltage Standing Wave Ratio Frequency Range: +0.0 to 5.0 gigahertz Attenuation Accuracy In Decibels: 0.50/+0.50 Frequency Sensitivity Attenuation In Decibels: 0.80 Temperature Sensitivity Attenuation In Decibels: 0.0005 Connection Type Per Function: Female input and male output Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range:	Body Material:
Round, terminal/terminals in opposite surface Body Surface Treatment: Silver plated Overall Length: 2.200 inches Overall Diameter: 0.650 inches Operating Tempurature Range: +0.0 to 80.0 degrees celsius Voltage Standing Wave Ratio: 1.30 Input Impedance Rating In Ohms: 50.0 Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: Tnc Power Rating: 2.0 watts average and 2.5 kilowatts peak Rf Signal Attenuation In Decibels: 10.0 Voltage Standing Wave Ratio Frequency Range: +0.0 to 5.0 gigahertz Attenuation Accuracy In Decibels: 0.80 Temperature Sensitivity Attenuation In Decibels: 0.80 Temperature Sensitivity Attenuation In Decibels: 0.0005 Connection Type Per Function: Female input and male output Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range:	Metal
Body Surface Treatment: Silver plated Overall Length: 2.200 inches Overall Diameter: 0.650 inches Operating Tempurature Range: +0.0 to 80.0 degrees celsius Voltage Standing Wave Ratio: 1.30 Input Impedance Rating In Ohms: 50.0 Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: Tnc Power Rating: 2.0 watts average and 2.5 kilowatts peak Rf Signal Attenuation In Decibels: 10.0 Voltage Standing Wave Ratio Frequency Range: +0.0 to 5.0 gigahertz Attenuation Accuracy In Decibels: 0.80 Temperature Sensitivity Attenuation In Decibels: 0.800 Temperature Sensitivity Attenuation In Decibels: 0.0005 Connection Type Per Function: Female input and male output Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range:	Body Style:
Silver plated Overall Length: 2.200 inches Overall Diameter: 0.650 inches Operating Tempurature Range: +0.0 to 80.0 degrees celsius Voltage Standing Wave Ratio: 1.30 Input Impedance Rating In Ohms: 50.0 Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: Tnc Power Rating: 2.0 watts average and 2.5 kilowatts peak Rf Signal Attenuation In Decibels: 10.0 Voltage Standing Wave Ratio Frequency Range: +0.0 to 5.0 gigahertz Attenuation Accuracy In Decibels: 0.80 Temperature Sensitivity Attenuation In Decibels: 0.0005 Connection Type Per Function: Female input and male output Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range:	Round, terminal/terminals in opposite surface
Overall Length: 2.200 inches Overall Diameter: 0.650 inches Operating Tempurature Range: +0.0 to 80.0 degrees celsius Voltage Standing Wave Ratio: 1.30 Input Impedance Rating In Ohms: 50.0 Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: Tnc Power Rating: 2.0 watts average and 2.5 kilowatts peak Rf Signal Attenuation In Decibels: 10.0 Voltage Standing Wave Ratio Frequency Range: +0.0 to 5.0 gigahertz Attenuation Accuracy In Decibels: -0.50/+0.50 Frequency Sensitivity Attenuation In Decibels: 0.80 Temperature Sensitivity Attenuation In Decibels: 0.0005 Connection Type Per Function: Female input and male output Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range:	Body Surface Treatment:
2.200 inches Overall Diameter: 0.650 inches Operating Tempurature Range: +0.0 to 80.0 degrees celsius Voltage Standing Wave Ratio: 1.30 Input Impedance Rating In Ohms: 50.0 Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: Tnc Power Rating: 2.0 watts average and 2.5 kilowatts peak Rf Signal Attenuation In Decibels: 10.0 Voltage Standing Wave Ratio Frequency Range: +0.0 to 5.0 gigahertz Attenuation Accuracy In Decibels: -0.50/+0.50 Frequency Sensitivity Attenuation In Decibels: 0.80 Temperature Sensitivity Attenuation In Decibels: 0.0005 Connection Type Per Function: Female input and male output Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range:	Silver plated
Overall Diameter: 0.650 inches Operating Tempurature Range: +0.0 to 80.0 degrees celsius Voltage Standing Wave Ratio: 1.30 Input Impedance Rating In Ohms: 50.0 Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: Tnc Power Rating: 2.0 watts average and 2.5 kilowatts peak Rf Signal Attenuation In Decibels: 10.0 Voltage Standing Wave Ratio Frequency Range: +0.0 to 5.0 gigahertz Attenuation Accuracy In Decibels: -0.50/+0.50 Frequency Sensitivity Attenuation In Decibels: 0.80 Temperature Sensitivity Attenuation In Decibels: 0.0005 Connection Type Per Function: Female input and male output Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range:	Overall Length:
Operating Tempurature Range: +0.0 to 80.0 degrees celsius Voltage Standing Wave Ratio: 1.30 Input Impedance Rating In Ohms: 50.0 Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: Tnc Power Rating: 2.0 watts average and 2.5 kilowatts peak Rf Signal Attenuation In Decibels: 10.0 Voltage Standing Wave Ratio Frequency Range: +0.0 to 5.0 gigahertz Attenuation Accuracy In Decibels: -0.50/+0.50 Frequency Sensitivity Attenuation In Decibels: 0.80 Temperature Sensitivity Attenuation In Decibels: 0.0005 Connection Type Per Function: Female input and male output Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range:	2.200 inches
Operating Tempurature Range: +0.0 to 80.0 degrees celsius Voltage Standing Wave Ratio: 1.30 Input Impedance Rating In Ohms: 50.0 Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: Tnc Power Rating: 2.0 watts average and 2.5 kilowatts peak Rf Signal Attenuation In Decibels: 10.0 Voltage Standing Wave Ratio Frequency Range: +0.0 to 5.0 gigahertz Attenuation Accuracy In Decibels: -0.50/+0.50 Frequency Sensitivity Attenuation In Decibels: 0.80 Temperature Sensitivity Attenuation In Decibels: 0.0005 Connection Type Per Function: Female input and male output Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range:	Overall Diameter:
+0.0 to 80.0 degrees celsius Voltage Standing Wave Ratio: 1.30 Input Impedance Rating In Ohms: 50.0 Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: Tnc Power Rating: 2.0 watts average and 2.5 kilowatts peak Rf Signal Attenuation In Decibels: 10.0 Voltage Standing Wave Ratio Frequency Range: +0.0 to 5.0 gigahertz Attenuation Accuracy In Decibels: -0.50/+0.50 Frequency Sensitivity Attenuation In Decibels: 0.80 Temperature Sensitivity Attenuation In Decibels: 0.0005 Connection Type Per Function: Female input and male output Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range:	0.650 inches
Voltage Standing Wave Ratio: 1.30 Input Impedance Rating In Ohms: 50.0 Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: Tnc Power Rating: 2.0 watts average and 2.5 kilowatts peak Rf Signal Attenuation In Decibels: 10.0 Voltage Standing Wave Ratio Frequency Range: +0.0 to 5.0 gigahertz Attenuation Accuracy In Decibels: -0.50/+0.50 Frequency Sensitivity Attenuation In Decibels: 0.80 Temperature Sensitivity Attenuation In Decibels: 0.0005 Connection Type Per Function: Female input and male output Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range:	Operating Tempurature Range:
Input Impedance Rating In Ohms: 50.0 Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: Tnc Power Rating: 2.0 watts average and 2.5 kilowatts peak Rf Signal Attenuation In Decibels: 10.0 Voltage Standing Wave Ratio Frequency Range: +0.0 to 5.0 gigahertz Attenuation Accuracy In Decibels: -0.50/+0.50 Frequency Sensitivity Attenuation In Decibels: 0.80 Temperature Sensitivity Attenuation In Decibels: 0.0005 Connection Type Per Function: Female input and male output Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range:	+0.0 to 80.0 degrees celsius
Input Impedance Rating In Ohms: 50.0 Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: Tnc Power Rating: 2.0 watts average and 2.5 kilowatts peak Rf Signal Attenuation In Decibels: 10.0 Voltage Standing Wave Ratio Frequency Range: +0.0 to 5.0 gigahertz Attenuation Accuracy In Decibels: -0.50/+0.50 Frequency Sensitivity Attenuation In Decibels: 0.80 Temperature Sensitivity Attenuation In Decibels: 0.0005 Connection Type Per Function: Female input and male output Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range:	Voltage Standing Wave Ratio:
Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: Tnc Power Rating: 2.0 watts average and 2.5 kilowatts peak Rf Signal Attenuation In Decibels: 10.0 Voltage Standing Wave Ratio Frequency Range: +0.0 to 5.0 gigahertz Attenuation Accuracy In Decibels: -0.50/+0.50 Frequency Sensitivity Attenuation In Decibels: 0.80 Temperature Sensitivity Attenuation In Decibels: 0.0005 Connection Type Per Function: Female input and male output Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range:	1.30
Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: Tnc Power Rating: 2.0 watts average and 2.5 kilowatts peak Rf Signal Attenuation In Decibels: 10.0 Voltage Standing Wave Ratio Frequency Range: +0.0 to 5.0 gigahertz Attenuation Accuracy In Decibels: -0.50/+0.50 Frequency Sensitivity Attenuation In Decibels: 0.80 Temperature Sensitivity Attenuation In Decibels: 0.0005 Connection Type Per Function: Female input and male output Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range:	Input Impedance Rating In Ohms:
Coaxial Connector Series Designation: Tnc Power Rating: 2.0 watts average and 2.5 kilowatts peak Rf Signal Attenuation In Decibels: 10.0 Voltage Standing Wave Ratio Frequency Range: +0.0 to 5.0 gigahertz Attenuation Accuracy In Decibels: -0.50/+0.50 Frequency Sensitivity Attenuation In Decibels: 0.80 Temperature Sensitivity Attenuation In Decibels: 0.0005 Connection Type Per Function: Female input and male output Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range:	50.0
Coaxial Connector Series Designation: Tnc Power Rating: 2.0 watts average and 2.5 kilowatts peak Rf Signal Attenuation In Decibels: 10.0 Voltage Standing Wave Ratio Frequency Range: +0.0 to 5.0 gigahertz Attenuation Accuracy In Decibels: -0.50/+0.50 Frequency Sensitivity Attenuation In Decibels: 0.80 Temperature Sensitivity Attenuation In Decibels: 0.0005 Connection Type Per Function: Female input and male output Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range:	Output Impedance Rating In Ohms:
Power Rating: 2.0 watts average and 2.5 kilowatts peak Rf Signal Attenuation In Decibels: 10.0 Voltage Standing Wave Ratio Frequency Range: +0.0 to 5.0 gigahertz Attenuation Accuracy In Decibels: -0.50/+0.50 Frequency Sensitivity Attenuation In Decibels: 0.80 Temperature Sensitivity Attenuation In Decibels: 0.0005 Connection Type Per Function: Female input and male output Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range:	50.0
Power Rating: 2.0 watts average and 2.5 kilowatts peak Rf Signal Attenuation In Decibels: 10.0 Voltage Standing Wave Ratio Frequency Range: +0.0 to 5.0 gigahertz Attenuation Accuracy In Decibels: -0.50/+0.50 Frequency Sensitivity Attenuation In Decibels: 0.80 Temperature Sensitivity Attenuation In Decibels: 0.0005 Connection Type Per Function: Female input and male output Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range:	Coaxial Connector Series Designation:
2.0 watts average and 2.5 kilowatts peak Rf Signal Attenuation In Decibels: 10.0 Voltage Standing Wave Ratio Frequency Range: +0.0 to 5.0 gigahertz Attenuation Accuracy In Decibels: -0.50/+0.50 Frequency Sensitivity Attenuation In Decibels: 0.80 Temperature Sensitivity Attenuation In Decibels: 0.0005 Connection Type Per Function: Female input and male output Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range:	Tnc
Rf Signal Attenuation In Decibels: 10.0 Voltage Standing Wave Ratio Frequency Range: +0.0 to 5.0 gigahertz Attenuation Accuracy In Decibels: -0.50/+0.50 Frequency Sensitivity Attenuation In Decibels: 0.80 Temperature Sensitivity Attenuation In Decibels: 0.0005 Connection Type Per Function: Female input and male output Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range:	Power Rating:
Voltage Standing Wave Ratio Frequency Range: +0.0 to 5.0 gigahertz Attenuation Accuracy In Decibels: -0.50/+0.50 Frequency Sensitivity Attenuation In Decibels: 0.80 Temperature Sensitivity Attenuation In Decibels: 0.0005 Connection Type Per Function: Female input and male output Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range:	2.0 watts average and 2.5 kilowatts peak
Voltage Standing Wave Ratio Frequency Range: +0.0 to 5.0 gigahertz Attenuation Accuracy In Decibels: -0.50/+0.50 Frequency Sensitivity Attenuation In Decibels: 0.80 Temperature Sensitivity Attenuation In Decibels: 0.0005 Connection Type Per Function: Female input and male output Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range:	Rf Signal Attenuation In Decibels:
+0.0 to 5.0 gigahertz Attenuation Accuracy In Decibels: -0.50/+0.50 Frequency Sensitivity Attenuation In Decibels: 0.80 Temperature Sensitivity Attenuation In Decibels: 0.0005 Connection Type Per Function: Female input and male output Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range:	10.0
Attenuation Accuracy In Decibels: -0.50/+0.50 Frequency Sensitivity Attenuation In Decibels: 0.80 Temperature Sensitivity Attenuation In Decibels: 0.0005 Connection Type Per Function: Female input and male output Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range:	Voltage Standing Wave Ratio Frequency Range:
-0.50/+0.50 Frequency Sensitivity Attenuation In Decibels: 0.80 Temperature Sensitivity Attenuation In Decibels: 0.0005 Connection Type Per Function: Female input and male output Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range:	+0.0 to 5.0 gigahertz
Frequency Sensitivity Attenuation In Decibels: 0.80 Temperature Sensitivity Attenuation In Decibels: 0.0005 Connection Type Per Function: Female input and male output Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range:	Attenuation Accuracy In Decibels:
O.80 Temperature Sensitivity Attenuation In Decibels: 0.0005 Connection Type Per Function: Female input and male output Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range:	-0.50/+0.50
Temperature Sensitivity Attenuation In Decibels: 0.0005 Connection Type Per Function: Female input and male output Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range:	Frequency Sensitivity Attenuation In Decibels:
0.0005 Connection Type Per Function: Female input and male output Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range:	0.80
Connection Type Per Function: Female input and male output Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range:	Temperature Sensitivity Attenuation In Decibels:
Female input and male output Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range:	0.0005
Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range:	Connection Type Per Function:
Connector Terminal Type And Quantity: 2 connector Frequency Range:	Female input and male output
Terminal Type And Quantity: 2 connector Frequency Range:	Mounting Method:
2 connector Frequency Range:	Connector
Frequency Range:	Terminal Type And Quantity:
	2 connector
Between 0.000 hertz and 750.000 megahertz	Frequency Range:
	Between 0.000 hertz and 750.000 megahertz

NSN 5985-00-138-7098

Fixed Attenuator - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A20000