

View Online at <https://aerobasegroup.com/nsn/5985-00-139-5973>

**Cross Sectional Shape:**

Internal, rectangular external, rectangular

**Tubing Wall Construction Style:**

Seamless single tubing segment

**Flange Quantity:**

2

**Voltage Standing Wave Ratio:**

1.15

**Insertion Loss In Decibels:**

0.30

**Maximum Operating Pressure:**

35.0 pounds per square inch gage

**Waveguide Outside Width:**

Between 0.699 inches and 0.705 inches

**Waveguide Inside Width:**

Between 0.6195 inches and 0.6245 inches

**Waveguide Inside Height:**

Between 0.3085 inches and 0.3135 inches

**Waveguide Outside Height:**

Between 0.388 inches and 0.394 inches

**Waveguide Longer Offset Distance:**

9.680 inches

**Waveguide Offset Distance:**

2.880 inches

**Flexibility:**

Flexible single tubing segment

**Material:**

Rubber synthetic single tubing jacket

**Precious Material And Location:**

Internal surfaces silver

**Precious Material:**

Silver

**Surface Treatment:**

Silver single tubing segment inside surfaces

**Style Designator:**

Bend type

**Fsc Application Data:**

Antennas, waveguides, and related equipment

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A073a0