## NSN 5985-00-140-8856

Fixed Attenuator - Page 1 of 2



<u> </u>
View Online at https://aerobasegroup.com/nsn/5985-00-140-8856
Application Design:
Transmission line
Body Material:
Steel, stainless
Body Style:
Round, terminal/terminals in opposite surface
Body Surface Treatment:
Passivated
Overall Length:
1.190 inches
Overall Diameter:
0.380 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.50
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Sma
Power Rating:
1.0 watts average
Rf Signal Attenuation In Decibels:
3.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+12.4 gigahertz
Attenuation Accuracy Reference Frequency:
12.4 gigahertz
Attenuation Accuracy In Decibels:
-0.60/+0.60
Connection Type Per Function:
Female input and male output
Mounting Method:
Connector

**Terminal Type And Quantity:** 

2 connector

Frequency Range:

Between 0.000 hertz and 12.400 gigahertz

**Fsc Application Data:** 

Antennas, waveguides, and related equipment

## NSN 5985-00-140-8856

Fixed Attenuator - Page 2 of 2



She	lf	Life:	
Oile	••	LIIV.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A20000