NSN 5985-00-140-9607

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-140-9607

view Online at https://derobasegroup.com/nsi//0300-00-140-3007
Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
4.250 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
Between 1.240 inches and 1.260 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
Between 1.802 inches and 1.822 inches
Overall Height:
3.800 inches
Overall Width:
Between 0.970 inches and 1.030 inches
Voltage Standing Wave Ratio:
1.51
Coaxial Connector Series Designation:
N
Power Rating:
4.0 watts average
Mounting Facility Screw Thread Series Designator:
Unc
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.5
Overall Attenuation Range In Decibels:
+0.0 to 30.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
4 threaded hole
Frequency Range:
Between 1.000 gigahertz and 8.000 gigahertz
Mounting Thread Quantity:
32 per inch
Adjustment Device Type And Quantity:
1 slotted screw
Mounting Facility Pattern:
Four position rectangular
Mounting Facility Screw Thread Diameter:
0.138 inches
Impedance Rating In Ohms:

50.0 input-output

NSN 5985-00-140-9607

Variable Attenuator - Page 2 of 2



Termina	I Type	And (Quantit	٧.
	11 1 1 1 1 1 1	Allu '	wuanni	ν.

1 connector, coaxial, male and 1 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0