## NSN 5985-00-145-3536

Variable Attenuator - Page 1 of 2

**Application Design:** 



View Online at https://aerobasegroup.com/nsn/5985-00-145-3536

| Transmission line                         |
|---|
| Body Style:                               |
| Coaxial type                              |
| Overall Length:                           |
| 6.000 inches                              |
| Overall Height:                           |
| 2.600 inches                              |
| Overall Width:                            |
| 2.750 inches                              |
| Scale Linearity:                          |
| Linear                                    |
| End Application:                          |
| Yellowstone class ad-41                   |
| Voltage Standing Wave Ratio:              |
| 1.20 and 1.30 and 1.50                    |
| Coaxial Connector Series Designation:     |
| Bnc                                       |
| Power Rating:                             |
| 0.5 watts average and 350.0 watts peak    |
| Overall Attenuation Range In Decibels:    |
| +0.0/+120.0                               |
| Attenuation Variation Method:             |
| Stepped                                   |
| Step Position Quantity:                   |
| 12  |
| Attenuation Per Step In Decibels:         |
| 10.0                                      |
| Mounting Facility Type And Quantity:      |
| 2 connector                               |
| Frequency Range:                          |
| Between 0.000 hertz and 1.000 gigahertz   |
| Overall Attenuation Accuracy In Decibels: |
| -0.30/+0.30                               |
| Adjustment Device Type And Quantity:      |
| 1 shaft and 1 knob                        |
| Criticality Code Justification:           |
| Feat                                      |
| Impedance Rating In Ohms:                 |
| 50.0 input-output                         |
| Special Features:                         |
| Weapon system essential                   |

## NSN 5985-00-145-3536

Variable Attenuator - Page 2 of 2



| Terminal | <b>Type</b> | And | Quantity | y: |
|----------|-------------|-----|----------|----|
|----------|-------------|-----|----------|----|

2 connector, coaxial, female

**Fsc Application Data:** 

Antennas, waveguides, and related equipment

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A223a0