NSN 5985-00-145-3539 Fixed Attenuator - Page 1 of 2



Fixed Attenuator - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/5985-00-145-3539
Application Design:
Transmission line
Body Material:
Any acceptable
Body Style:
Round, terminal/terminals in opposite surface
Body Surface Treatment:
Any acceptable
Overall Length:
2.438 inches
Overall Diameter:
0.813 inches
Operating Tempurature Range:
Any acceptable
Voltage Standing Wave Ratio:
1.20
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
N
Power Rating:
2.0 watts average and 100.0 watts peak
Rf Signal Attenuation In Decibels:
10.0
Voltage Standing Wave Ratio Frequency Range:
+0.0 to 18.0 gigahertz
Attenuation Accuracy In Decibels:
-1.50 to 1.50
Frequency Sensitivity Attenuation In Decibels:
Not rated
Temperature Sensitivity Attenuation In Decibels:
Not rated
Connection Type Per Function:

Mounting Method: Connector

Terminal Type And Quantity:

2 connector

Frequency Range:

Between 0.000 hertz and 18.000 gigahertz

Female input-output and male input-output

NSN 5985-00-145-3539

Fixed Attenuator - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A20000