## NSN 5985-00-145-9437

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-145-9437 **Application Design:** Audio **Body Style:** Cylindrical w/side terminals **Overall Length:** 1.407 inches **Overall Width:** 0.836 inches **Body Diameter:** 0.672 inches **Shaft Diameter:** 0.125 inches **Bushing Length:** 0.375 inches **Shaft Length:** 0.688 inches **Body Length:** 0.719 inches **Schematic Diagram Designator:** Bridged "t" **Operating Tempurature Range:** +40.0 to 120.0 degrees celsius **Power Rating:** 250.0 milliwatts average **Mounting Facility Screw Thread Series Designator:** Unef **Insertion Loss At Minimum Attenuation In Maximum Decibels:** 0.5 **Overall Attenuation Range In Decibels:** +0.5 to 40.0 **Attenuation Variation Method:** Continuous **Mounting Facility Type And Quantity:** 1 threaded bushing **Mounting Thread Quantity:** 32 per inch **Adjustment Device Type And Quantity:** 1 shaft **Shaft Type:** 

Round

**Mounting Facility Screw Thread Diameter:** 

0.250 inches

## NSN 5985-00-145-9437

Variable Attenuator - Page 2 of 2



Impedance Rating In Ohms	lm	pedance	Rating	In	<b>Ohms</b>
--------------------------	----	---------	--------	----	-------------

600.0 input-output

**Terminal Type And Quantity:** 

4 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A223a0