

View Online at <https://aerobasegroup.com/nsn/5985-00-145-9438>

Thread Class:

2b mounting facility hole

Body Style:

Irregular

Overall Length:

2.500 inches

Overall Height:

2.000 inches

Overall Width:

1.990 inches

Frequency Rating:

0.0 gigahertz and 2.0 gigahertz single frequency voltage standing wave ratio

Switch Type:

Transfer

Longest Horizontal Distance Between Mounting Centers:

1.750 inches single mounting facility pattern

Longest Vertical Distance Between Mounting Centers:

0.562 inches single mounting facility pattern

Operating Temperature Range:

-54.0/+100.0 degrees celsius

Voltage Standing Wave Ratio:

1.50 single

Insertion Loss In Decibels:

0.15 single

Coaxial Connector Series Designation:

Tnc

Connector End Design:

Female

Rf Power Handling Capability:

10.0 watts average single

Minimum Crosstalk Rating In Decibels:

17.0 single

Actuator Operating Method:

Relay

Actuator Current Type And Rating In Amps:

0.1 dc

Actuator Voltage In Volts:

26.0

Switch Operation Sequence:

Breaks before makes

Switching Time:

25.0 milliseconds

Switch Return Mechanism Type:

Fail-safe

Rf Maximum Voltage Rating:

1.0 kilovolts peak

Coupling Position Quantity:

4

Mounting Facility Type And Quantity:

8 threaded hole

Thread Size:

0.112 inches mounting facility hole

Mounting Facility Pattern:

Eight position rectangular single mounting facility pattern

Special Features:

Double mtg w/four mtg holes ea side

Material:

Metal body

Thread Series Designator:

Unc mounting facility hole

Terminal Type And Quantity:

2 tab, solder lug and 4 receptacle, coaxial

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A158a0