## NSN 5985-00-146-4831

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-146-4831

Application Design:
Transmission line
Body Material:
Steel, stainless
Body Style:
Round, terminal/terminals in opposite surface
Overall Length:
1.150 inches
Overall Diameter:
Any acceptable
Operating Tempurature Range:
-55.0 to 125.0 degrees celsius
Voltage Standing Wave Ratio:
1.25 and 1.30
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Sma
Power Rating:
1.0 watts average and 1.0 kilowatts peak
Rf Signal Attenuation In Decibels:
20.0
Voltage Standing Wave Ratio Frequency Range:
+0.0 to 5.0 gigahertz and +5.0 to 7.0 gigahertz
Attenuation Accuracy In Decibels:
-0.50 to 0.50
Frequency Sensitivity Attenuation In Decibels:
Not rated
Temperature Sensitivity Attenuation In Decibels:
Not rated
Connection Type Per Function:
Female output and male input
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 7.000 gigahertz
Shelf Life:
N/a

## NSN 5985-00-146-4831

Fixed Attenuator - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A20000