NSN 5985-00-146-4833

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-146-4833

Application Designs
Application Design: Transmission line
Body Style:
Coaxial type
Overall Length:
2.500 inches
Overall Height:
1.800 inches
Overall Width:
0.500 inches
Operating Tempurature Range:
-55.0 to 125.0 degrees celsius
Voltage Standing Wave Ratio:
1.50
Coaxial Connector Series Designation:
Mfm
Power Rating:
2.0 watts average and 1.0 kilowatts peak
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.5
Overall Attenuation Range In Decibels:
+10.0 to 30.0
Attenuation Accuracy Reference Frequency:
6.0 gigahertz
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
2 connector
Frequency Range:
Between 2.000 gigahertz and 12.400 gigahertz
Overall Attenuation Accuracy In Decibels:
-0.50/+0.50
Adjustment Device Type And Quantity:
1 slotted screw
Impedance Rating In Ohms:
50.0 input-output
Terminal Type And Quantity:
2 connector, coaxial, female
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5985-00-146-4833

Variable Attenuator - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A223a0