NSN 5985-00-147-0079

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-147-0079

Application Design:
Transmission line
Body Material:
Aluminum
Body Style:
Coaxial type
Overall Length:
3.700 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.875 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.000 inches
Overall Height:
2.375 inches
Overall Width:
0.625 inches
Unthreaded Mounting Hole Diameter:
0.147 inches
Operating Tempurature Range:
+0.0/+60.0 degrees celsius
Voltage Standing Wave Ratio:
2.00
Coaxial Connector Series Designation:
Mm
Power Rating:
2.0 watts average
Insertion Loss At Minimum Attenuation In Maximum Decibels:
2.8
Overall Attenuation Range In Decibels:
+2.8/+45.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
4 unthreaded hole
Frequency Range:
Between 8.000 gigahertz and 18.000 gigahertz
Adjustment Device Type And Quantity:
1 electronic, programmable
Mounting Facility Pattern:
Four position rectangular
Impedance Rating In Ohms:

50.0 input-output

NSN 5985-00-147-0079

Variable Attenuator - Page 2 of 2



Precious	Material	∆nd ∣	Location:

Connectors gold

Precious Material:

Gold

Terminal Type And Quantity:

3 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0