NSN 5985-00-147-9011



Variable Attenuator - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5985-00-147-9011 **Application Design:** Waveguide **Body Style:** Waveguide type **Overall Length:** 3.875 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 2.875 inches **Center To Center Distance Between Mounting Facilities Parallel To Width:** 1.250 inches **Overall Height:** 2.156 inches **Overall Width:** 3.606 inches **Unthreaded Mounting Hole Diameter:** 0.203 inches **Operating Tempurature Range:** -54.0 to 71.0 degrees celsius **Voltage Standing Wave Ratio:** 1.50 **Power Rating:** 0.5 watts average **Waveguide Flange Type:** Choke **Waveguide Flange Designation:** Ug-541a/u **Insertion Loss At Minimum Attenuation In Maximum Decibels:** 0.5 **Overall Attenuation Range In Decibels:** +0.0 to 40.0 **Attenuation Variation Method:** Continuous **Mounting Facility Type And Quantity:** 4 unthreaded hole Frequency Range: Between 12.400 gigahertz and 18.000 gigahertz **Adjustment Device Type And Quantity:** 1 knob

Mounting Facility Pattern:

Four position rectangular

Terminal Type And Quantity:

2 flange

NSN 5985-00-147-9011

Variable Attenuator - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0