## NSN 5985-00-150-0415

Fixed Attenuator - Page 1 of 2

**Application Design:** Transmission line



View Online at https://aerobasegroup.com/nsn/5985-00-150-0415

Body Material:
Aluminum
Body Style:
Rectangular, terminal/terminals on opposite surfaces
Terminal Material:
Steel, stainless
Terminal Surface Treatment:
Passivated
Body Surface Treatment:
Anodized
Overall Length:
5.375 inches
Overall Height:
Between 2.470 inches and 2.530 inches
Overall Width:
Between 2.470 inches and 2.530 inches
Operating Tempurature Range:
-20.0/+70.0 degrees celsius
End Application:
Test set, radio an/arm-156
Voltage Standing Wave Ratio:
1.10
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
N
Power Rating:
20.0 watts average and 10.0 kilowatts peak
Rf Signal Attenuation In Decibels:
10.0
Voltage Standing Wave Ratio Frequency Range:
+960.0/+1215.0 megahertz
Attenuation Accuracy In Decibels:
-0.15/+0.15
Temperature Sensitivity Attenuation In Decibels:
0.0001
Connection Type Per Function:

Male input and female output

## **NSN 5985-00-150-0415** Fixed Attenuator - Page 2 of 2



Unpackaged Unit Weight:
995.0 grams
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 1.500 gigahertz
Specification Data:
57057-880330001 manufacturers specification control
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
Yes - demil/mli
Fiig:

A20000