

View Online at <https://aerobasegroup.com/nsn/5985-00-150-1009>

Thread Class:

2b mounting facility hole

Body Style:

Irregular

Overall Length:

3.391 inches

Overall Height:

2.375 inches

Overall Width:

1.375 inches

Frequency Rating:

0.0 gigahertz and 6.0 gigahertz single frequency voltage standing wave ratio

Switch Type:

Nontransfer

Longest Horizontal Distance Between Mounting Centers:

1.328 inches single mounting facility pattern

Longest Vertical Distance Between Mounting Centers:

1.032 inches single mounting facility pattern

Operating Temperature Range:

-55.0 to 100.0 degrees celsius

Voltage Standing Wave Ratio:

1.50 single

Insertion Loss In Decibels:

0.30 single

Coaxial Connector Series Designation:

Bnc

Connector End Design:

Female

Rf Power Handling Capability:

500.0 watts average single

Minimum Crosstalk Rating In Decibels:

50.0 single

Actuator Operating Method:

Relay

Actuator Voltage In Volts:

26.0

Switch Operation Sequence:

Breaks before makes

Switching Time:

25.0 milliseconds

Switch Return Mechanism Type:

Fail-safe

Pole Quantity:

2

Throw Quantity:

2

Rf Maximum Voltage Rating:

1.0 kilovolts peak

Coupling Position Quantity:

6

Mounting Facility Type And Quantity:

4 threaded hole

Thread Size:

0.112 inches mounting facility hole

Mounting Facility Pattern:

Four position rectangular single mounting facility pattern

Special Features:

Double mtg w/four holes ea side

Material:

Metal body

Surface Treatment:

Enamel body outside surfaces

Thread Series Designator:

Unc mounting facility hole

Terminal Type And Quantity:

3 tab, solder lug and 6 receptacle, coaxial

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A158a0