

View Online at <https://aerobasegroup.com/nsn/5985-00-150-1029>

**Thread Class:**

2b mounting facility hole

**Body Style:**

Irregular

**Overall Length:**

2.375 inches

**Overall Height:**

1.375 inches

**Overall Width:**

1.688 inches

**Frequency Rating:**

0.0 gigahertz and 6.0 gigahertz single frequency voltage standing wave ratio

**Switch Type:**

Nontransfer

**Longest Horizontal Distance Between Mounting Centers:**

1.032 inches single mounting facility pattern

**Longest Vertical Distance Between Mounting Centers:**

0.750 inches single mounting facility pattern

**Operating Temperature Range:**

-55.0 to 100.0 degrees celsius

**Voltage Standing Wave Ratio:**

1.50 single

**Insertion Loss In Decibels:**

0.50 single

**Coaxial Connector Series Designation:**

Bnc

**Connector End Design:**

Female

**Rf Power Handling Capability:**

500.0 watts average single

**Minimum Crosstalk Rating In Decibels:**

36.0 single

**Actuator Operating Method:**

Relay

**Actuator Voltage In Volts:**

26.0

**Switch Operation Sequence:**

Breaks before makes

**Switching Time:**

25.0 milliseconds

**Pole Quantity:**

1

**Throw Quantity:**

2

**Rf Maximum Voltage Rating:**

1.0 kilovolts peak

**Coupling Position Quantity:**

3

**Mounting Facility Type And Quantity:**

4 threaded hole

**Thread Size:**

0.112 inches mounting facility hole

**Mounting Facility Pattern:**

Four position rectangular single mounting facility pattern

**Special Features:**

Double mtg w/four holes ea side

**Material:**

Metal body

**Surface Treatment:**

Enamel body outside surfaces

**Thread Series Designator:**

Unc mounting facility hole

**Terminal Type And Quantity:**

2 turret and 3 receptacle, coaxial

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A158a0