

View Online at <https://aerobasegroup.com/nsn/5985-00-153-0119>

**Application Design:**

Transmission line

**Body Style:**

Coaxial type

**Overall Length:**

4.250 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.250 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.812 inches

**Overall Height:**

1.000 inches

**Overall Width:**

3.850 inches

**Shaft Diameter:**

0.250 inches

**Shaft Length:**

1.730 inches

**Voltage Standing Wave Ratio:**

1.50

**Coaxial Connector Series Designation:**

N

**Power Rating:**

4.0 watts average

**Mounting Facility Screw Thread Series Designator:**

Unc

**Insertion Loss At Minimum Attenuation In Maximum Decibels:**

0.5

**Overall Attenuation Range In Decibels:**

+0.0 to 30.0

**Attenuation Variation Method:**

Continuous

**Mounting Facility Type And Quantity:**

4 threaded hole

**Frequency Range:**

Between 4.400 gigahertz and 5.000 gigahertz

**Overall Attenuation Accuracy In Decibels:**

-1.00 to 1.00

**Mounting Thread Quantity:**

32 per inch

**Adjustment Device Type And Quantity:**

1 shaft

**Mounting Facility Pattern:**

Four position rectangular

**Shaft Type:**

Round, slotted

**Mounting Facility Screw Thread Diameter:**

0.138 inches

**Impedance Rating In Ohms:**

50.0 input-output

**Precious Material And Location:**

Terminals rhodium and terminals silver

**Precious Material:**

Rhodium and silver

**Terminal Type And Quantity:**

1 connector, coaxial, female and 1 connector, coaxial, male

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A223a0