## NSN 5985-00-155-0764

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-155-0764

Application Design:
Transmission line
Body Material:
Steel, stainless
Body Style:
Round, terminal/terminals in opposite surface
Body Surface Treatment:
Bright alloy
Overall Length:
1.150 inches
Overall Diameter:
0.350 inches
Operating Tempurature Range:
-46.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.25 and 1.30
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Sm
Power Rating:
Power Rating: 2.0 watts average and 1.0 kilowatts peak
_
2.0 watts average and 1.0 kilowatts peak
2.0 watts average and 1.0 kilowatts peak  Rf Signal Attenuation In Decibels:
2.0 watts average and 1.0 kilowatts peak  Rf Signal Attenuation In Decibels:  30.0
2.0 watts average and 1.0 kilowatts peak  Rf Signal Attenuation In Decibels:  30.0  Voltage Standing Wave Ratio Frequency Range:
2.0 watts average and 1.0 kilowatts peak  Rf Signal Attenuation In Decibels:  30.0  Voltage Standing Wave Ratio Frequency Range: +0.0/+5.0 gigahertz and +5.0/+7.0 gigahertz
2.0 watts average and 1.0 kilowatts peak  Rf Signal Attenuation In Decibels: 30.0  Voltage Standing Wave Ratio Frequency Range: +0.0/+5.0 gigahertz and +5.0/+7.0 gigahertz  Attenuation Accuracy In Decibels:
2.0 watts average and 1.0 kilowatts peak  Rf Signal Attenuation In Decibels: 30.0  Voltage Standing Wave Ratio Frequency Range: +0.0/+5.0 gigahertz and +5.0/+7.0 gigahertz  Attenuation Accuracy In Decibels: -1.00/+1.00
2.0 watts average and 1.0 kilowatts peak  Rf Signal Attenuation In Decibels: 30.0  Voltage Standing Wave Ratio Frequency Range: +0.0/+5.0 gigahertz and +5.0/+7.0 gigahertz  Attenuation Accuracy In Decibels: -1.00/+1.00  Temperature Sensitivity Attenuation In Decibels:
2.0 watts average and 1.0 kilowatts peak  Rf Signal Attenuation In Decibels: 30.0  Voltage Standing Wave Ratio Frequency Range: +0.0/+5.0 gigahertz and +5.0/+7.0 gigahertz  Attenuation Accuracy In Decibels: -1.00/+1.00  Temperature Sensitivity Attenuation In Decibels: 0.00003
2.0 watts average and 1.0 kilowatts peak  Rf Signal Attenuation In Decibels: 30.0  Voltage Standing Wave Ratio Frequency Range: +0.0/+5.0 gigahertz and +5.0/+7.0 gigahertz  Attenuation Accuracy In Decibels: -1.00/+1.00  Temperature Sensitivity Attenuation In Decibels: 0.00003  Connection Type Per Function:
2.0 watts average and 1.0 kilowatts peak  Rf Signal Attenuation In Decibels: 30.0  Voltage Standing Wave Ratio Frequency Range: +0.0/+5.0 gigahertz and +5.0/+7.0 gigahertz  Attenuation Accuracy In Decibels: -1.00/+1.00  Temperature Sensitivity Attenuation In Decibels: 0.00003  Connection Type Per Function: Female output and male input
2.0 watts average and 1.0 kilowatts peak  Rf Signal Attenuation In Decibels: 30.0  Voltage Standing Wave Ratio Frequency Range: +0.0/+5.0 gigahertz and +5.0/+7.0 gigahertz  Attenuation Accuracy In Decibels: -1.00/+1.00  Temperature Sensitivity Attenuation In Decibels: 0.00003  Connection Type Per Function: Female output and male input  Mounting Method:
2.0 watts average and 1.0 kilowatts peak  Rf Signal Attenuation In Decibels: 30.0  Voltage Standing Wave Ratio Frequency Range: +0.0/+5.0 gigahertz and +5.0/+7.0 gigahertz  Attenuation Accuracy In Decibels: -1.00/+1.00  Temperature Sensitivity Attenuation In Decibels: 0.00003  Connection Type Per Function: Female output and male input  Mounting Method: Connector
2.0 watts average and 1.0 kilowatts peak  Rf Signal Attenuation In Decibels: 30.0  Voltage Standing Wave Ratio Frequency Range: +0.0/+5.0 gigahertz and +5.0/+7.0 gigahertz  Attenuation Accuracy In Decibels: -1.00/+1.00  Temperature Sensitivity Attenuation In Decibels: 0.00003  Connection Type Per Function: Female output and male input  Mounting Method: Connector  Terminal Type And Quantity:
2.0 watts average and 1.0 kilowatts peak  Rf Signal Attenuation In Decibels: 30.0  Voltage Standing Wave Ratio Frequency Range: +0.0/+5.0 gigahertz and +5.0/+7.0 gigahertz  Attenuation Accuracy In Decibels: -1.00/+1.00  Temperature Sensitivity Attenuation In Decibels: 0.00003  Connection Type Per Function: Female output and male input  Mounting Method: Connector  Terminal Type And Quantity: 2 connector
2.0 watts average and 1.0 kilowatts peak  Rf Signal Attenuation In Decibels: 30.0  Voltage Standing Wave Ratio Frequency Range: +0.0/+5.0 gigahertz and +5.0/+7.0 gigahertz  Attenuation Accuracy In Decibels: -1.00/+1.00  Temperature Sensitivity Attenuation In Decibels: 0.00003  Connection Type Per Function: Female output and male input  Mounting Method: Connector  Terminal Type And Quantity: 2 connector  Frequency Range:

## NSN 5985-00-155-0764

Fixed Attenuator - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A20000