NSN 5985-00-157-4882

Waveguide Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5985-00-157-4882

| View Online at https://aerobasegroup.com/nsn/5 |
|--|
| Cross Sectional Shape: |
| Internal, rectangular external, rectangular |
| Tubing Wall Construction Style: |
| Seamless single tubing segment |
| Flange Quantity: |
| 2 |
| Voltage Standing Wave Ratio: |
| 1.10 |
| Maximum Operating Pressure: |
| 30.0 pounds per square inch gage |
| Waveguide Outside Width: |
| Between 0.699 inches and 0.705 inches |
| Waveguide Inside Width: |
| Between 0.6195 inches and 0.6245 inches |
| Waveguide Inside Height: |
| Between 0.3085 inches and 0.3135 inches |
| Waveguide Outside Height: |
| Between 0.388 inches and 0.394 inches |
| Waveguide Length: |
| 4.340 inches |
| Waveguide Center To Center Distance: |
| 1.500 inches |
| Flexibility: |
| Rigid single tubing segment |
| Material: |
| Aluminum alloy all tubing segment and flange |
| Surface Treatment: |
| Nickel all flange all surfaces |
| Style Designator: |
| Offset bend type |
| Fsc Application Data: |
| Antennas, waveguides, and related equipment |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig:

A073a0