

View Online at <https://aerobasegroup.com/nsn/5985-00-159-7343>

**Body Style:**

Rectangular

**Overall Length:**

2.970 inches

**Overall Height:**

1.090 inches

**Overall Width:**

2.670 inches

**Frequency Rating:**

0.0 kilohertz and 11.0 kilohertz single frequency operating 0.0 kilohertz and 11.0 kilohertz single frequency voltage standing wave ratio 0.0 kilohertz and 11.0 kilohertz single frequency insertion loss reference 0.0 kilohertz and 11.0 kilohertz single frequency crosstalk reference

**Unthreaded Mounting Hole Diameter:**

0.203 inches

**Switch Type:**

Nontransfer

**Distance Between Mounting Facility Centers:**

0.885 inches single mounting facility pattern

**Operating Temperature Range:**

-65.0 to 185.0 degrees fahrenheit

**Voltage Standing Wave Ratio:**

1.50 single

**Insertion Loss In Decibels:**

0.50 single

**Coaxial Connector Series Designation:**

N

**Connector End Design:**

Female

**Minimum Crosstalk Rating In Decibels:**

60.0 single

**Actuator Operating Method:**

Relay

**Actuator Current Type And Rating In Amps:**

0.5 dc

**Actuator Voltage In Volts:**

26.0

**Switch Operation Sequence:**

Makes before breaks

**Switching Time:**

50.0 milliseconds

**Switch Return Mechanism Type:**

Latching

**Pole Quantity:**

1

**Throw Quantity:**

2

**Coupling Position Quantity:**

3

**Mounting Facility Type And Quantity:**

2 unthreaded hole

**Mounting Facility Pattern:**

Two position in-line single mounting facility pattern

**Material:**

Aluminum body

**Terminal Type And Quantity:**

3 tab w/screw and 3 plug, coaxial

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A158a0