NSN 5985-00-160-2296

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-160-2296

| Application Design: |
|---|
| Transmission line |
| Body Style: |
| Coaxial type |
| Overall Length: |
| 6.937 inches |
| Overall Height: |
| 2.875 inches |
| Overall Width: |
| 5.500 inches |
| Scale Linearity: |
| Linear |
| Scale Division Quantity: |
| 10 |
| Operating Tempurature Range: |
| +2.0/+38.0 degrees celsius |
| Voltage Standing Wave Ratio: |
| 1.50 |
| Coaxial Connector Series Designation: |
| N |
| Power Rating: |
| 2.0 watts peak |
| Insertion Loss At Minimum Attenuation In Maximum Decibels: |
| 0.8 |
| Overall Attenuation Range In Decibels: |
| +0.0 to 10.0 |
| Attenuation Accuracy Reference Frequency: |
| 500.0 megahertz |
| Attenuation Variation Method: |
| Continuous |
| Frequency Range: |
| Between 0.000 hertz and 1.000 gigahertz |
| Overall Attenuation Accuracy In Decibels: |
| -0.20 to 0.20 |
| Adjustment Device Type And Quantity: |
| 1 knob |
| Impedance Rating In Ohms: |
| 50.0 input-output |
| Terminal Type And Quantity: |
| 1 connector, coaxial, male and 1 connector, coaxial, female |
| Shelf Life: |

N/a

NSN 5985-00-160-2296

Variable Attenuator - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0