

View Online at <https://aerobasegroup.com/nsn/5985-00-160-5464>

**Thread Class:**

2b mounting facility hole

**Body Style:**

Irregular

**Overall Length:**

3.096 inches

**Overall Height:**

1.938 inches

**Overall Width:**

1.500 inches

**Frequency Rating:**

0.0 gigahertz and 2.0 gigahertz single frequency voltage standing wave ratio

**Switch Type:**

Transfer

**Distance Between Mounting Facility Centers:**

1.032 inches single mounting facility pattern

**Operating Temperature Range:**

-55.0 to 100.0 degrees celsius

**Voltage Standing Wave Ratio:**

1.20 single

**Insertion Loss In Decibels:**

0.15 single

**Coaxial Connector Series Designation:**

N

**Connector End Design:**

Female

**Rf Power Handling Capability:**

3.0 kilowatts peak single

**Minimum Crosstalk Rating In Decibels:**

25.0 single

**Actuator Operating Method:**

Relay

**Actuator Current Type And Rating In Amps:**

0.1 dc

**Actuator Voltage In Volts:**

26.0

**Switch Operation Sequence:**

Breaks before makes

**Switching Time:**

25.0 milliseconds

**Switch Return Mechanism Type:**

Fail-safe

**Rf Maximum Voltage Rating:**

1.0 kilovolts peak

**Coupling Position Quantity:**

4

**Mounting Facility Type And Quantity:**

4 threaded hole

**Thread Size:**

0.112 inches mounting facility hole

**Mounting Facility Pattern:**

Two position in-line single mounting facility pattern

**Material:**

Aluminum body

**Surface Treatment:**

Enamel body outside surfaces

**Thread Series Designator:**

Unc mounting facility hole

**Terminal Type And Quantity:**

2 turret and 4 receptacle, coaxial

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A158a0