NSN 5985-00-160-9519

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-160-9519

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
5.940 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.500 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.250 inches
Overall Height:
2.570 inches
Overall Width:
2.790 inches
Unthreaded Mounting Hole Diameter:
0.213 inches
Operating Tempurature Range:
-65.0 to 125.0 degrees celsius
Voltage Standing Wave Ratio:
1.20 and 1.30
Coaxial Connector Series Designation:
Bnc
Bnc Power Rating:
Power Rating:
Power Rating: 0.5 watts average and 350.0 watts peak
Power Rating: 0.5 watts average and 350.0 watts peak Overall Attenuation Range In Decibels:
Power Rating: 0.5 watts average and 350.0 watts peak Overall Attenuation Range In Decibels: +0.0/+12.0
Power Rating: 0.5 watts average and 350.0 watts peak Overall Attenuation Range In Decibels: +0.0/+12.0 Attenuation Accuracy Reference Frequency:
Power Rating: 0.5 watts average and 350.0 watts peak Overall Attenuation Range In Decibels: +0.0/+12.0 Attenuation Accuracy Reference Frequency: 1.0 kilohertz
Power Rating: 0.5 watts average and 350.0 watts peak Overall Attenuation Range In Decibels: +0.0/+12.0 Attenuation Accuracy Reference Frequency: 1.0 kilohertz Attenuation Variation Method:
Power Rating: 0.5 watts average and 350.0 watts peak Overall Attenuation Range In Decibels: +0.0/+12.0 Attenuation Accuracy Reference Frequency: 1.0 kilohertz Attenuation Variation Method: Stepped
Power Rating: 0.5 watts average and 350.0 watts peak Overall Attenuation Range In Decibels: +0.0/+12.0 Attenuation Accuracy Reference Frequency: 1.0 kilohertz Attenuation Variation Method: Stepped Step Position Quantity:
Power Rating: 0.5 watts average and 350.0 watts peak Overall Attenuation Range In Decibels: +0.0/+12.0 Attenuation Accuracy Reference Frequency: 1.0 kilohertz Attenuation Variation Method: Stepped Step Position Quantity: 12
Power Rating: 0.5 watts average and 350.0 watts peak Overall Attenuation Range In Decibels: +0.0/+12.0 Attenuation Accuracy Reference Frequency: 1.0 kilohertz Attenuation Variation Method: Stepped Step Position Quantity: 12 Attenuation Per Step In Decibels:
Power Rating: 0.5 watts average and 350.0 watts peak Overall Attenuation Range In Decibels: +0.0/+12.0 Attenuation Accuracy Reference Frequency: 1.0 kilohertz Attenuation Variation Method: Stepped Step Position Quantity: 12 Attenuation Per Step In Decibels: 1.0
Power Rating: 0.5 watts average and 350.0 watts peak Overall Attenuation Range In Decibels: +0.0/+12.0 Attenuation Accuracy Reference Frequency: 1.0 kilohertz Attenuation Variation Method: Stepped Step Position Quantity: 12 Attenuation Per Step In Decibels: 1.0 Mounting Facility Type And Quantity:
Power Rating: 0.5 watts average and 350.0 watts peak Overall Attenuation Range In Decibels: +0.0/+12.0 Attenuation Accuracy Reference Frequency: 1.0 kilohertz Attenuation Variation Method: Stepped Step Position Quantity: 12 Attenuation Per Step In Decibels: 1.0 Mounting Facility Type And Quantity: 4 bracket
Power Rating: 0.5 watts average and 350.0 watts peak Overall Attenuation Range In Decibels: +0.0/+12.0 Attenuation Accuracy Reference Frequency: 1.0 kilohertz Attenuation Variation Method: Stepped Step Position Quantity: 12 Attenuation Per Step In Decibels: 1.0 Mounting Facility Type And Quantity: 4 bracket Frequency Range:
Power Rating: 0.5 watts average and 350.0 watts peak Overall Attenuation Range In Decibels: +0.0/+12.0 Attenuation Accuracy Reference Frequency: 1.0 kilohertz Attenuation Variation Method: Stepped Step Position Quantity: 12 Attenuation Per Step In Decibels: 1.0 Mounting Facility Type And Quantity: 4 bracket Frequency Range: Between 0.000 hertz and 500.000 megahertz

2 knob

NSN 5985-00-160-9519

Variable Attenuator - Page 2 of 2



Mounting Facility Patterr	Μοι	ınting	Facility	Pattern
---------------------------	-----	--------	----------	---------

Four position rectangular

Impedance Rating In Ohms:

50.0 input-output

Terminal Type And Quantity:

4 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0