## NSN 5985-00-162-9293

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-162-9293 **Application Design:** Transmission line **Body Material:** Steel, stainless **Body Style:** Round, terminal/terminals in opposite surface **Body Surface Treatment:** Enamel **Overall Length:** 1.250 inches **Overall Diameter:** 0.500 inches **Voltage Standing Wave Ratio:** 1.20 and 1.30 Input Impedance Rating In Ohms: 50.0 **Output Impedance Rating In Ohms:** 50.0 **Coaxial Connector Series Designation:** Osm **Power Rating:** 2.0 watts average and 100.0 watts peak **Rf Signal Attenuation In Decibels:** 6.0 **Voltage Standing Wave Ratio Frequency Range:** +0.0/+8.0 gigahertz and +8.0/+12.4 gigahertz **Attenuation Accuracy In Decibels:** -0.30/+0.30 **Connection Type Per Function:** Female output and male input **Mounting Method:** Connector **Terminal Type And Quantity:** 2 connector Frequency Range: Between 0.000 gigahertz and 12.400 gigahertz Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5985-00-162-9293

Fixed Attenuator - Page 2 of 2



Fiig:

A20000