## NSN 5985-00-163-7760

Variable Attenuator - Page 1 of 2



Vie	ew Online at https://aerobasegroup.com/nsn/5985-00-163-7760
Ap	pplication Design:
Tra	ansmission line
Во	ody Style:
Co	axial type
Ov	verall Length:
Ве	tween 3.568 inches and 3.932 inches
Во	olt Circle Diameter:
3.3	375 inches
Ov	verall Height:
2.0	000 inches
Sc	ale Linearity:
Lin	near
Sc	ale Division Quantity:
20	
Vo	Itage Standing Wave Ratio:
1.0	00 and 1.80
Co	paxial Connector Series Designation:
Ν	
Po	wer Rating:
10	.0 watts average
Мо	ounting Facility Screw Thread Series Designator:
Un	ic .
Ov	verall Attenuation Range In Decibels:
+0	.0/+20.0
At	tenuation Variation Method:
Ste	epped
Ste	ep Position Quantity:
20	
At	tenuation Per Step In Decibels:
1.0	
Мо	ounting Facility Type And Quantity:
3 t	hreaded hole
Fre	equency Range:
Ве	tween 4.200 gigahertz and 4.400 gigahertz
Мс	ounting Thread Quantity:
32	per inch

**Adjustment Device Type And Quantity:** 

1 knob

**Mounting Facility Pattern:** 

Three position circular

**Mounting Facility Screw Thread Diameter:** 

0.164 inches

## NSN 5985-00-163-7760

Variable Attenuator - Page 2 of 2



Terminal Type And Quanti	ty	:
--------------------------	----	---

2 connector, coaxial, female

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0