NSN 5985-00-166-0811

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-166-0811

Cross Sectional Shape:

Internal, rectangular external, rectangular

Tubing Wall Construction Style:

Corrugated single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.003 inches all flanges and 1.006 inches all flanges

Flange Inside Height:

0.503 inches all flanges and 0.506 inches all flanges

Flange Outside Width:

1.610 inches all flanges and 1.640 inches all flanges

Flange Outside Height:

1.610 inches all flanges and 1.640 inches all flanges

Flange Depth:

0.423 inches all flanges and 0.453 inches all flanges

Flange Connecting Hole Diameter:

0.169 inches all flanges all connection facilities and 0.172 inches all flanges all connection facilities

Voltage Standing Wave Ratio:

1.15

Insertion Loss In Decibels:

0.10

Maximum Operating Pressure:

120.0 pounds per square inch gage

Waveguide Outside Width:

1.250 inches

Waveguide Inside Height:

0.656 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole all flanges all connection facilities

Flange Style:

Cover type all flanges

Flexibility:

Flexible single tubing segment

Material:

Aluminum alloy all flange

Precious Material And Location:

Flange surface silver

Precious Material:

Silver

Surface Treatment:

Silver all flange inside surfaces

NSN 5985-00-166-0811

Waveguide Assembly - Page 2 of 2



Style Designator:
Bend type
Fsc Application Data:
Antennas, waveguides, and related equipment
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig: A073a0