

View Online at <https://aerobasegroup.com/nsn/5985-00-168-9400>

**Cross Sectional Shape:**

Internal, rectangular external, rectangular

**Thread Class:**

2b first flange all connection facilities

**Thread Direction:**

Right-hand first flange all connection facilities

**Tubing Wall Construction Style:**

Seamless single tubing segment

**Flange Quantity:**

2

**Flange Inside Width:**

1.253 inches second flange

**Flange Inside Height:**

0.628 inches second flange

**Flange Outside Width:**

1.875 inches second flange

**Flange Outside Height:**

1.875 inches second flange

**Flange Depth:**

0.625 inches first flange

**Flange Connecting Hole Diameter:**

0.169 inches second flange all connection facilities

**Voltage Standing Wave Ratio:**

1.05

**Insertion Loss In Decibels:**

0.04

**Thready Qty Per Inch (tpi):**

32 first flange all connection facilities

**Maximum Operating Pressure:**

30.0 pounds per square inch gage

**Waveguide Outside Width:**

Between 1.246 inches and 1.254 inches

**Thread Size:**

0.164 inches first flange all connection facilities

**Waveguide Inside Width:**

Between 1.118 inches and 1.126 inches

**Waveguide Inside Height:**

Between 0.493 inches and 0.501 inches

**Waveguide Outside Height:**

Between 0.621 inches and 0.629 inches

**Flange Connecting Facility And Quantity:**

4 unthreaded hole second flange all connection facilities

**Flange Style:**

Cover type second flange

**Waveguide Length:**

Between 1.303 feet and 1.363 feet

**Waveguide Center To Center Distance:**

Between 2.220 inches and 2.280 inches

**Flexibility:**

Rigid single tubing segment

**Material:**

Any acceptable single tubing segment

**Surface Treatment:**

Any acceptable single tubing segment all surfaces

**Style Designator:**

Offset bend type

**Thread Series Designator:**

Unc first flange all connection facilities

**Fsc Application Data:**

Countermeasures set

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A073a0