# NSN 5985-00-168-9470

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-168-9470

#### **Cross Sectional Shape:**

Internal, rectangular external, rectangular

#### Bend Angle In Deg:

90.0 all bends e-plane

#### **Tubing Wall Construction Style:**

Seamless single tubing segment

## **Tubing Twist Type:**

Straight twist single tubing segment

#### **Tubing Twist Angle In Deg:**

45.0 single tubing segment

Flange Quantity:

2

#### **Voltage Standing Wave Ratio:**

1.10

#### **Maximum Operating Pressure:**

20.0 pounds per square inch gage

#### **Waveguide Outside Width:**

1.500 inches

# **Waveguide Inside Width:**

1.372 inches

# **Waveguide Inside Height:**

0.622 inches

#### **Waveguide Outside Height:**

0.750 inches

### **Waveguide Longer Offset Distance:**

Between 21.980 inches and 22.020 inches

#### **Waveguide Offset Distance:**

Between 13.730 inches and 13.770 inches

# Special Features:

Frequency band 7.9 to 8.4 ghz

### Flexibility:

Rigid single tubing segment

#### Material:

Aluminum alloy all tubing segment and flange

#### **Surface Treatment:**

Anodize all tubing segment and flange all surfaces

### Style Designator:

Bend type

#### **Fsc Application Data:**

Radar equipment

#### Shelf Life:

N/a

# NSN 5985-00-168-9470

Waveguide Assembly - Page 2 of 2



**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A073a0