

View Online at <https://aerobasegroup.com/nsn/5985-00-169-3680>

Application Design:

Transmission line

Body Material:

Steel, stainless

Body Style:

Round, terminal/terminals in opposite surface

Terminal Material:

Beryllium copper

Terminal Surface Treatment:

Gold plated

Body Surface Treatment:

Passivated

Overall Length:

0.750 inches

Overall Diameter:

0.250 inches

Operating Temperature Range:

-55.0 to 125.0 degrees celsius

Voltage Standing Wave Ratio:

1.15 and 1.25 and 1.60 and 1.80

Input Impedance Rating In Ohms:

50.0

Output Impedance Rating In Ohms:

50.0

Coaxial Connector Series Designation:

Sma

Power Rating:

2.0 watts average

Rf Signal Attenuation In Decibels:

10.0

Voltage Standing Wave Ratio Frequency Range:

+0.0 to 4.0 gigahertz and +4.1/+12.0 gigahertz and +12.1/+15.0 gigahertz and +15.1 to 18.0 gigahertz

Connection Type Per Function:

Female input and male output

Mounting Method:

Connector

Terminal Type And Quantity:

2 connector

Frequency Range:

Between 0.000 hertz and 18.000 gigahertz

Precious Material And Location:

Connector pins gold

Precious Material:

Gold

Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A20000