

View Online at <https://aerobasegroup.com/nsn/5985-00-169-3680>

**Application Design:**

Transmission line

**Body Material:**

Steel, stainless

**Body Style:**

Round, terminal/terminals in opposite surface

**Terminal Material:**

Beryllium copper

**Terminal Surface Treatment:**

Gold plated

**Body Surface Treatment:**

Passivated

**Overall Length:**

0.750 inches

**Overall Diameter:**

0.250 inches

**Operating Temperature Range:**

-55.0 to 125.0 degrees celsius

**Voltage Standing Wave Ratio:**

1.15 and 1.25 and 1.60 and 1.80

**Input Impedance Rating In Ohms:**

50.0

**Output Impedance Rating In Ohms:**

50.0

**Coaxial Connector Series Designation:**

Sma

**Power Rating:**

2.0 watts average

**Rf Signal Attenuation In Decibels:**

10.0

**Voltage Standing Wave Ratio Frequency Range:**

+0.0 to 4.0 gigahertz and +4.1/+12.0 gigahertz and +12.1/+15.0 gigahertz and +15.1 to 18.0 gigahertz

**Connection Type Per Function:**

Female input and male output

**Mounting Method:**

Connector

**Terminal Type And Quantity:**

2 connector

**Frequency Range:**

Between 0.000 hertz and 18.000 gigahertz

**Precious Material And Location:**

Connector pins gold

**Precious Material:**

Gold

**Fsc Application Data:**

Antennas, waveguides, and related equipment

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A20000