NSN 5985-00-172-0643

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-172-0643

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange single connection facility

Thread Direction:

Right-hand first flange single connection facility

Bend Angle In Deg:

90.0 single bend e-plane

End Application:

Radar set an/gpn-12

Tubing Wall Construction Style:

Seamless all tubing segment

Flange Quantity:

2

Flange Inside Width:

3.002 inches second flange

Flange Inside Height:

1.502 inches second flange

Flange Outside Diameter:

5.298 inches first flange and 5.328 inches first flange

Flange Depth:

1.235 inches first flange and 1.265 inches first flange

Flange Connecting Hole Diameter:

0.257 inches second flange single connection facility

Thready Qty Per Inch (tpi):

20 first flange single connection facility

Waveguide Outside Width:

Between 2.994 inches and 3.006 inches

Thread Size:

0.250 inches first flange single connection facility

Waveguide Inside Width:

Between 2.834 inches and 2.846 inches

Waveguide Inside Height:

Between 1.334 inches and 1.346 inches

Waveguide Outside Height:

Between 1.494 inches and 1.506 inches

Waveguide Longer Offset Distance:

Between 3.395 inches and 3.415 inches

Flange Connecting Facility And Quantity:

8 unthreaded hole second flange single connection facility

Flange Style:

Cover type second flange

NSN 5985-00-172-0643

Waveguide Assembly - Page 2 of 2

Demilitarization: Yes - demil/mli

Fiig: A073a0



Waveguide Offset Distance:
Between 3.395 inches and 3.415 inches
Flexibility:
Rigid all tubing segment
Material:
Aluminum alloy all tubing segment and flange
Surface Treatment:
Primer all tubing segment and flange outside surfaces and paint all tubing segment and flange outside surfaces
Style Designator:
Bend type
Thread Series Designator:
Unc first flange single connection facility
Fsc Application Data:
Antennas, waveguides, and related equipment
Shelf Life:
N/a
Unit Of Measure:
<u></u>