

View Online at <https://aerobasegroup.com/nsn/5985-00-172-4614>

**Application Design:**

Transmission line

**Body Style:**

Coaxial type

**Overall Length:**

4.500 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.500 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.500 inches

**Overall Width:**

4.500 inches

**Coaxial Connector Series Designation:**

N

**Power Rating:**

5.0 watts average and 500.0 watts peak

**Mounting Facility Screw Thread Series Designator:**

Unc

**Insertion Loss At Minimum Attenuation In Maximum Decibels:**

6.0

**Overall Attenuation Range In Decibels:**

+0.0/+60.0

**Attenuation Accuracy Reference Frequency:**

2.0 gigahertz

**Attenuation Variation Method:**

Continuous

**Mounting Facility Type And Quantity:**

4 threaded hole

**Frequency Range:**

Between 0.000 hertz and 4.000 gigahertz

**Overall Attenuation Accuracy In Decibels:**

-1.00/+1.00

**Mounting Thread Quantity:**

32 per inch

**Adjustment Device Type And Quantity:**

1 lever

**Mounting Facility Pattern:**

Four position rectangular

**Mounting Facility Screw Thread Diameter:**

0.164 inches

**Impedance Rating In Ohms:**

50.0 input-output

**Terminal Type And Quantity:**

2 connector, coaxial, female

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A223a0