NSN 5985-00-172-4942

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-172-4942

| Application | Design: |
|-------------|---------|
| Application | Design. |

Transmission line

Body Style:

Coaxial type

Overall Length:

4.500 inches

Overall Height:

2.818 inches

Overall Width:

1.936 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.938 inches

Distance Between Mounting Facility Centers:

1.125 inches

Voltage Standing Wave Ratio:

1.06

Coaxial Connector Series Designation:

Bnc

Power Rating:

250.0 milliwatts average

Mounting Facility Screw Thread Series Designator:

Unc

Insertion Loss At Minimum Attenuation In Maximum Decibels:

0.05

Overall Attenuation Range In Decibels:

+0.0 to 80.0

Attenuation Variation Method:

Stepped

Step Position Quantity:

8

Attenuation Per Step In Decibels:

10.0

Mounting Facility Type And Quantity:

2 threaded hole

Frequency Range:

Between 0.000 hertz and 32.000 megahertz

Overall Attenuation Accuracy In Decibels:

-0.10 to 0.01

Mounting Thread Quantity:

32 per inch

NSN 5985-00-172-4942

Variable Attenuator - Page 2 of 2



Adjustment Device Type And Quantity:

1 shaft

Mounting Facility Pattern:

Two position in-line

Shaft Type:

Round

Mounting Facility Screw Thread Diameter:

0.164 inches

Impedance Rating In Ohms:

75.0 input-output

Terminal Type And Quantity:

2 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A223a0