## NSN 5985-00-172-6259

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-172-6259

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
4.375 inches
Overall Height:
3.750 inches
Overall Width:
2.625 inches
Voltage Standing Wave Ratio:
1.50
Coaxial Connector Series Designation:
Npm
Power Rating:
2.0 watts average and 200.0 watts peak
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.05
Overall Attenuation Range In Decibels:
+0.0 to 69.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
69
Attenuation Per Step In Decibels:
1.0
Mounting Facility Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 12.400 gigahertz
Segment Attenuation Range In Decibels:
+0.00 to 1.00 and +1.00/+9.00 and +10.00 to 19.00 and +20.00/+29.00 and +30.00/+39.00 and +40.00 to 49.00 and +50.00 to 59.00 and
+60.00 to 69.00
Segment Attenuation Accuracy In Decibels:
-0.60 to 0.60 and -0.40 to 0.40 and -1.00/+1.00 and -1.20/+1.20 and -1.40/+0.40 and -1.50/+1.50 and -1.70 to 1.70 and -1.80 to 1.80
Adjustment Device Type And Quantity:
2 knob
Impedance Rating In Ohms:
50.0 input-output
Terminal Type And Quantity:
2 connector, coaxial, female
Shelf Life:

N/a

## NSN 5985-00-172-6259

Variable Attenuator - Page 2 of 2



**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0